



MATERIAL SAFETY DATA SHEET

SUBJECT : UPS F. 101
Industrial Floor Cleaner

Manufactures by : WESTERS INDUSTRIES, PT
Jl. Industri Selatan 10 Blok EE No. 11B Jababeka
industrial District **Cikarang** – Indonesia
Emergency call : [6221-89841382](tel:6221-89841382)
Website : www.westers-ind.com
Email : info@westers-ind.com

Page 1 of 2

UPS F. 101 Industrial Floor Cleaner

I. DESCRIPTION :

For use in automatic scrubbing machines, mop and baskets and pump tank sprayer application. **UPS F. 101** is a super power full low foam, cold water stripper, is guaranteed to remove metallized or conventional finishes and waxes faster than you can say “ ONE TWO THREE”. A blend of three special solvents and two wetting agents attacks heavy wax or polymer build ups, keeping it suspended for easy rinsing. **UPS F. 101** performs a function that regular finish removers cannot, 'lifting' that extra tough coating.

II. FEATURES :

- ❖ SAFE – Excellent for use on terrazzo, cork, asphalt, cements, vinyl, tile and linoleum.
- ❖ LOW SUDSING – foam reducing agents prevent foam clogging of automatic scrubbing machine.
- ❖ EFFICIENT – strip metallic interlock polymers faster and with less labor.
- ❖ HIGHLY CONCENTRATED – lower stripping costs.
- ❖ Leaves none of the soapy scum or residue of ordinary strippers.

III. COMPOSITION AND PROPERTIES :

A blend of synthetic penetrate, biodegradable surfactants, in organic builders and solvents provide superior stripping in all dilutions.

IV. APPLICATIONS :

Mop or spray liberal amounts of **UPS F. 101** to the floor. Allow approximately 5 minutes for **UPS F. 101** to do the job. Scrub or brush or stripping pad is preferred to clear the loosen wax and dirt. Rinse the floor with clean water. Allow the floor to dry through before applying new floor finish.

LIGHT STRIPPING

Of medium build UPS

1 : 8 parts of water

SURFACE STRIPPING

Of removing the finish and leaving the sealer in tack.

1 : 10 parts of water



MATERIAL SAFETY DATA SHEET

**SUBJECT : UPS F. 101
Industrial Floor Cleaner**

Manufactures by : WESTERS INDUSTRIES, PT
Jl. Industri Selatan 10 Blok EE No. 11B Jababeka
industrial District **Cikarang** – Indonesia
Emergency call : [6221-89841382](tel:6221-89841382)
Website : www.westers-ind.com
Email : info@westers-ind.com

Page 2 of 2

V. SAFETY DATA

EYES : If contact lenses are worn, remove immediately and flush with water for at least 15 minutes.

SKIN : Avoid prolonged contact with skin. In use wear cotton gloves.

Keep out of mouth and avoid prolonged breathing of its vapors.

If poisoning occurs, contact poisons information center or a doctor.